



amma earth product 5-873 Technical Information Sheet

wood soap

DESCRIPTION

Use Volvox Hardwood Floor Renovator for care and maintenance of Volvox oil finished timber floors and furniture. The product is adjusted to rejuvenate heavily used and worn out oil finished surfaces. It is also suitable to remove stains and marks.

APPLICATIONS

REGULAR CARE

Stir product well and add up to 20 ml. to 10 litre of water. Use this solution to mop the floor clean.

WIPE SURFACE DRY AFTER.

REJUVENATING

Mop floor clean. Stir product well. Apply one very thin coat of Volvox Hardwood Floor Renovator with a moist (water) mop or cloth. Repeat application until surface appears rejuvenated. Mob off soap residues and **WIPE SURFACE DRY AFTER.**

MARKS AND STAINS

Stir product well and apply to the effected area. Work the product in grain direction into the timber using a cloth or lightly abrasive Scotch pad (white). Wipe clean after with some water or moist mop. **WIPE SURFACE DRY AFTER.**

CLEAN UP

Clean tools immediately with water after use.

STORAGE

Store product cool, frost-free and in tightly sealed container.

INGREDIENTS

Flax Seed Oil, Wood Oil, Rosin, Beeswax, Carnauba Wax, Lead free dryers, Preservative, Seed oil soap.

SAFETY

Working rags and other fabrics soaked with oil may self-ignite. Let dry safely outdoors on a cloth line or store in a sealed metal container. The product by itself will not self-ignite.

Even if non-toxic, keep away from children.

DISPOSAL

Allow unwanted oil to dry. Solid matter should be disposed of via the normal garbage collection service.

DISCLAIMER

The user is recommended to test the product on the intended surface to ensure its suitability.

HANDY HINTS AND TRICKS FOR FRESHLY OILED FINISHED FLOORS

Treat your fresh oiled surface with care since oil needs to harden for a period of 2 – 3 weeks.

NO WATER ON THE OILED SURFACE.

After that a moist mobbing is possible. Do not use any detergent or other additives in the mobbing water. **WIPE SURFACE DRY AFTER.**

Avoid micro fire mobs as they will extract oil from the timber.

Note that oil finished surfaces are permeable to vapour while fluids and dirt is repelled. Some vapour of liquids can penetrate the protective oil layer and can react with substances in the wood such as tannic acid causing slight stains. These can easily be removed by adding 20 ml. Volvox Hardwood Floor Renovator 5-871 to 10 litre of mobbing water. Moist mob the floor and **WIPE SURFACE DRY AFTER.**

We recommend your oil finished floor to be checked and maintained by your professional floor sander as we guarantee the quality of the product only. We cannot guarantee for care and maintenance of a floor.

For further information contact

Amma Earth Products

Phone: 02 47 82 90 09

info@amma.net.au

www.amma.net.au